



Sabaplast 70 T

SABA, a strong bond

Description

Sabaplast 70 T is a one- or two-component polyurethane adhesive based on flammable solvents for the bonding of soft PVC foils. Sabaplast 70 T is especially appropriate for water resistant bondings.

Solvent based adhesives

Special properties

- Plasticizer resistant
- Soft bond line
- High temperature resistance
- Water resistant
- Transparent

MSP sealants

Water based adhesives

Method of use

Apply by brush. Clean surface eventually with SABA Cleaner 21. Bond both parts, assemble parts within 10 minutes and press well. Mix adhesive eventually with 5 weight percents SABA Vulk L for improved water resistance and temperature resistance.

Silicone sealants

Foam coatings

Technical data

Viscosity at 23 °C	:	approx. 2500 mPa.s
Density	:	approx. 880 kg/m ³
Solids content	:	approx. 20%
Open time	:	two-sidedly up to 10 minutes
Curing time	:	approx. 24 hours
Coverage	:	approx. 200 g/m ²
Clean with	:	SABA Cleaner 21
Work temperature	:	minimum + 15 °C (R.H. not above 70%)
Storage temperature	:	minimum + 5 °C and maximum + 35 °C
Temperature resistance	:	one-component approx. + 60 °C two-component approx. + 85 °C
Shelf life	:	12 months in unopened packing

Hotmelts

Epoxy products

PU products

Polysulfide products

Order information

Primers

Cleaning agents

Packing	100 ml tin with brush	250 ml tin with cap and brush	1 litre can with cover	6 litres can with cap	30 litres can with cap	200 litres drum
Contents				5 kg	25 kg	176 kg

Colour	natural
Article No.	100138

Safety indications

See the corresponding material safety data sheet.



SABA Dinxperlo BV

Industriestraat 3, NL-7091 DC Dinxperlo, PO Box 3, NL-7090 AA Dinxperlo, the Netherlands,
Tel +31 (0) 315 658999, Fax +31 (0) 315 653207, E-mail info@saba.nl, Internet www.saba.nl.

Our recommendations and instructions for use are based on the present status of know-how and technique. Clients and users should evaluate our products by themselves, with regard to utilization and requirements of their own choice. We shall take no responsibility in case our products are not being used subject to our recommendations and/or instructions for use. Furthermore, General Terms and Conditions of the Dutch Association "Nederlandse Vereniging van Rubber en Kunststoffabrikanten of January 1, 1992", will apply to our recommendations, instructions for use and the delivery of our products.

Version number: 2006/03